

Chem-Crest[®] 75A

Phosphoric acid-based ultrasonic Liquid detergent concentrate



Description

Chem-Crest 75A is phosphoric acid based cleaner. The product is designed for removing oils, greases, lubricants and oxides. It is capable of producing hydrophilic surfaces upon rinsing with water. It is used typically for the brightening of soft metals as well as the removal of greases, oxides, and particulates, but finds uses in many different applications. Chem-Crest 75A is also part of the Crest Aqueous Displacement System series of detergents.

Typical Contaminants Removed

Chem-Crest 75A is effective at removal of light oxides from the surface of soft metal and stainless steel parts, as well as oils, tinctures, greases, and lubricants. Chem-Crest 75A will brighten dull appearances and leave no residue upon proper rinsing. It is recommended that an ultrasonic rinse follow applications using Chem-Crest 75A.

Physical Data

Flash Point: None

Specific Gravity: 1.15 +/- 0.07

pH: 1 % solution = 2.2 +/- 0.5

Solubility in Water: Complete

Volatiles: N/A

**These are typical values and do not constitute specifications.

Storage Conditions and Disposal Methods

Avoid freezing conditions. Dispose in accordance with Federal, State, and Local regulations and procedures. Chem-Crest 75A contains Phosphoric Acid (CAS# 7664-38-2), and is subject to regulation under SARA Title III, Section 313.

Safety Precautions

See Safety Data Sheet

Operating Conditions

Chem-Crest 75A is used at typical dilution of 4 – 10 % by volume. Concentration may vary based on the type of the organic film. Typical operating temperature is in the range of 50°C - 65°C. Chem-Crest 75A is easy to rinse and leaves no residues when ultrasonically rinse with deionized water. In certain cases, a rust inhibitor, such as the Chem-Crest 77 series rinse injection line, will be necessary after use of Chem-Crest 75A.

Substrate Compatibility

Chem Crest 75A is compatible with 300 series stainless steel, titanium and various plastic components. It is not recommended for use with precious metals and should be tested before use on aluminum or copper-containing materials, high-carbon steels, and other materials.

Availability

Chem-Crest 75A is available in cases of (4) x 1-gallon plastic bottles, 5-gallon pails, and in 55-gallon containers. It is also available in bulk containers.

For further information on this product, please contact the Chemical Sales Office at:

Crest Ultrasonics Corporation

18 Graphics Drive | Ewing, NJ 08628 | USA

Office +1.609.883.4000 x219

Sjoyce@crest-ultrasonics.com

www.crest-ultrasonics.com

Crest Ultrasonics maintains sales offices in the United States, Malaysia, Singapore, Japan, Germany, the United Kingdom, India, and France.

Our chemicals are blended at our Philadelphia, PA office, Custom Blends, Inc. – A Division of Crest Ultrasonics.

Disclaimer: All statements, technical information and recommendation contained herein are based on tests or other information available to us which we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and are made without representation or warranty. They are presented for your own investigation and verification. Products discussed are sold without warranty, expressed or implied, in law or fact and upon the condition that purchasers make their own tests to determine the suitability of such products to their particular purpose. We shall not be liable for any injury, loss or damage direct or consequential, arising out of use or the inability to use the product. It is the user's obligation and responsibility to determine that any use of the product or the information may infringe on patent rights.